



Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: SX100
Print date: 26.09.2021
Version: 27-0

SX100
Revision date: 26.09.2022
Issue date:

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 PRODUCT IDENTIFIERS
Article No. (manufacturer/supplier) SX100
Identification of the substance or mixture SX100
- 1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST
- 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET
Details of the supplier of the safety data sheet
Qualitape UK Ltd
Unit 1 Sarah Court
Haverhill
Suffolk
CB9 8PA

Website : www.qualitape.co.uk
- 1.4 EMERGENCY TELEPHONE NUMBER
Emergency telephone number 01440 710747
Only available during office hours.

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE*
Classification according to Regulation (EC) No. 1272/2008 [CLP]
The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].
- | | | |
|----------------------|-----------------------------------|-------------------------------------|
| Flam. Liq. 2 / H225 | Flammable liquids | Highly flammable liquid and vapour. |
| Skin Irrit. 2 / H315 | Skin corrosion/irritation | Causes skin irritation. |
| Eye Irrit. 2 / H319 | Serious eye damage/eye irritation | Causes serious eye irritation. |

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.:	SX100	SX100
Print date:	26.09.2021	Revision date: 26.09.2022
Version: 27-0		Issue date:

STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

2.2

LABEL ELEMENTS*

Labelling according to Regulation (EC. 1272/2008 [CLP]
Hazard pictograms



Danger

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use extinguishing powder or sand to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Keep locked up.
P501	Dispose of contents/container to industrial incineration plant.

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: SX100
Print date: 26.09.2021
Version: 27-0

SX100
Revision date: 26.09.2022
Issue date:

Contains: propan-2-ol
Hydrocarbon C7-9, n-alcane, is
Supplemental Hazard information (EU): not applicable

2.3 OTHER HAZARDS

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.2 MIXTURES
Product description / chemical characterization
Description: Colour

Hazardous ingredients
Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name Classification // Remark	Wt %
200-661-7 67-63-0 603-117-00-0	01-2119457558-25 propan-2-ol Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	30 - 50
927-510-4	01-2119475515-33 Hydrocarbon C7-9, n-alcane, is Flam. Liq. 2 H225 / Skin Irrit. 2 H315 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336	30 - 50
203-625-9 108-88-3 601-021-00-3	01-2119471310-51 Toluene Flam. Liq. 2 H225 / Repr. 2 H361 / Asp. Tox. 1 H304 / STOT RE 2 H373 / Skin Irrit. 2 H315 / STOT SE 3 H336	1 - 5

Additional information
Full text of classification: See Section 16

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.:
Print date:
Version: 27-0

SX100
26.09.2021

SX100
Revision date: 26.09.2022
Issue date:

SECTION 4: FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES

General information:

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation:

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion:

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm.

Do NOT induce vomiting.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

SECTION 5: FIREFIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Suitable extinguishing media: alcohol resistant foam, carbon dioxide, Powder, spray mist, (water).

Extinguishing media which must not be used for safety reasons: strong water jet

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: SX100
Print date: 26.09.2021
Version: 27-0

SX100
Revision date: 26.09.2022
Issue date:

5.3 ADVICE FOR FIREFIGHTERS

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES
Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2 ENVIRONMENTAL PRECAUTIONS
Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP
Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see Section 13). Clean using cleansing agents. Do not use solvents.

6.4 REFERENCE TO OTHER SECTIONS
Observe protective provisions (see Section 7 and Section 8).

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Advices on safe handling:
Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8.

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.:	SX100	SX100
Print date:	26.09.2021	Revision date: 26.09.2022
Version: 27-0		Issue date:

Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion
Vapours are heavier than air. Vapours form explosive mixtures with air

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Requirements for storage rooms and vessels:
Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges.

Hints on joint storage:
Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions:
Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3 SPECIFIC END USE(S)

Observe technical data sheet. Observe instructions for use.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Occupational exposure limit values:
propan-2-ol
INDEX No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

WEL, TWA: 999 mg/m³; 400 ppm
WEL, STEL: 1250 mg/m³; 500 ppm

Toluene
INDEX No. 601-021-00-3 / EC No. 203-625-9 / CAS No. 108-88-3

WEL, TWA: 191 mg/m³; 50 ppm
WEL, STEL: 384 mg/m³; 100 ppm

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: SX100
Print date: 26.09.2021
Version: 27-0

SX100
Revision date: 26.09.2022
Issue date:

Additional information

TWA: long-term occupational exposure limit value
STEL: short-term occupational exposure limit value
Ceiling: peak limitation

DNEL:

Toluene
INDEX No. 601-021-00-3 / EC No. 203-625-9 / CAS No. 108-88-3

DNEL long-term dermal (systemic), Workers: 384 mg/kg
DNEL acute inhalative (local), Workers: 384 mg/m³
DNEL acute inhalative (systemic), Workers: 384 mg/m³
DNEL long-term inhalative (local), Workers: 192 mg/m³
DNEL short-term oral (acute), Consumer: 226 mg/kg
DNEL long-term dermal (systemic), Consumer: 226 mg/kg
DNEL acute inhalative (local), Consumer: 226 mg/m³
DNEL long-term inhalative (systemic), Consumer: 56,5 mg/m³

PNEC:

Toluene
INDEX No. 601-021-00-3 / EC No. 203-625-9 / CAS No. 108-88-3
PNEC aquatic, freshwater: 0,68 mg/l
PNEC aquatic, marine water: 0,68 mg/l
PNEC sediment, freshwater: 16,39 mg/kg
PNEC sediment, marine water: 16,39 mg/kg
PNEC, soil: 2,89 mg/kg
PNEC sewage treatment plant (STP): 13,61 mg/l

8.2

EXPOSURE CONTROLS

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

OCCUPATIONAL EXPOSURE CONTROLS

Respiratory protection:

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: SX100
Print date: 26.09.2021
Version: 27-0

SX100
Revision date: 26.09.2022
Issue date:

Hand protection:

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material > 0,4 mm; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection:

Wear closely fitting protective glasses in case of splashes.

Protective clothing:

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures:

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls:

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES*

Appearance:

Physical state:	Liquid
Colour:	refer to label
Odour:	characteristic
Odour threshold:	not applicable
pH at 20 °C:	not applicable
Melting point / freezing point:	not applicable
Initial boiling point and boiling range:	82 °C
Flash point:	Source: propan-2-ol -5 °C Method: DIN 53213
Evaporation rate:	not applicable
Flammability (solid, gas):	
Burning time(s):	not applicable

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.:	SX100	SX100
Print date:	26.09.2021	Revision date: 26.09.2022
Version: 27-0		Issue date:

Upper/lower flammability or explosive limits:

Lower explosion limit:	2 Vol-%
Upper explosion limit:	12 Vol-%
	Source: propan-2-ol
Vapour pressure at 20 °C:	23,689 mbar
Vapour density:	not applicable
Relative density:	
Density at 20 °C:	0,75 g/cm ³
Solubility(ies):	
Water solubility (g/L) at 20 °C:	miscible
Partition coefficient: n-octanol/water:	see Section 12

Auto-ignition temperature:	246 °C
	Source: Hydrocarbon C7-9, n-alcane, is
Decomposition temperature:	not applicable
Viscosity at 20 °C:	11 s 4 mm
	Method: DIN 53211
Explosive properties:	not applicable
Oxidising properties:	not applicable

9.2

OTHER INFORMATION

Solid content (%):	2,09 Wt %
Solvent content:	
Organic solvents:	98 Wt %
Water:	0 Wt %

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY: None known

10.2 CHEMICAL STABILITY

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 CONDITIONS TO AVOID

Hazardous decomposition byproducts may form with exposure to high temperatures.

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.:	SX100	SX100
Print date:	26.09.2021	Revision date: 26.09.2022
Version: 27-0		Issue date:

10.5 INCOMPATIBLE MATERIALS

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Classification according to Regulation (EC) No 1272/2008 [CLP].
No data on preparation itself available.

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS*

Acute toxicity

Toluene

oral, LD50, Rat: 5580 mg/kg

dermal, LD50, Rabbit: > 5000 mg/kg

inhalative (vapours), LC50, Rat: 28,1 mg/l (4 h)

propan-2-ol

oral, LD50, Rat: 5840 mg/kg

dermal, LD50, Rabbit: 13900 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation:
Toxicological data are not available.

Respiratory or skin sensitization:
Toxicological data are not available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):
Toxicological data are not available.

Specific target organ toxicity:
Toxicological data are not available.

Aspiration hazard:
Toxicological data are not available.

Practical experience/human evidence

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: SX100
Print date: 26.09.2021
Version: 27-0

SX100
Revision date: 26.09.2022
Issue date:

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: ECOLOGICAL INFORMATION

Overall evaluation:

Classification according to Regulation (EC) No. 1272/2008 [CLP].

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

12.1

TOXICITY*

Toluene

Fish toxicity, LC50: 5,5 mg/l (96 h)

Daphnia toxicity, EC50: 3,8 mg/l (48 h)

Algae toxicity, ErC50: 12,5 mg/l

propan-2-ol

Fish toxicity, LC50: 9640 mg/l (96 h)

12.2

PERSISTENCE AND DEGRADABILITY

Toxicological data are not available.

12.3

BIOACCUMULATIVE POTENTIAL

Toxicological data are not available.

12.4

MOBILITY IN SOIL

Toxicological data are not available.

12.5

RESULTS OF PBT AND vPvB ASSESSMENT

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.:	SX100	SX100
Print date:	26.09.2021	Revision date: 26.09.2022
Version: 27-0		Issue date:

12.6 OTHER ADVERSE EFFECTS

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 Waste paint and varnish containing organic solvents or other dangerous substances

Packaging Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: TRANSPORT INFORMATION

14.1 UN NUMBER UN 1263

14.2 UN PROPER SHIPPING NAME
Land transport (ADR/RID): Paint
Sea transport (IMDG): PAINT
Air transport (ICAO-TI / IATA-DGR): Paint

14.3 TRANSPORT HAZARD CLASS(ES) 3

14.4 PACKING GROUP II

14.5 ENVIRONMENTAL HAZARDS
Land transport (ADR/RID) UMWELTGEFÄHRDEND

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: SX100
Print date: 26.09.2021
Version: 27-0

SX100
Revision date: 26.09.2022
Issue date:

Marine pollutant

p / Hydrocarbon C7-9, n-alcane, is

14.6

SPECIAL PRECAUTIONS FOR USER

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 – 8

Further information

Land transport (ADR/RID)

Tunnel restriction code: D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

Air transport (ICAO-TI / IATA-DGR)

14.7

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL AND THE IBC CODE

Not applicable

SECTION 15: REGULATORY INFORMATION

15.1

SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

EU legislation

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 737

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2

CHEMICAL SAFETY ASSESSMENT

For the following substances of this preparation of a chemical safety assessment has been carried out:

Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: SX100
Print date: 26.09.2021
Version: 27-0

SX100
Revision date: 26.09.2022
Issue date:

EC No. CAS No.	Chemical name	REACH No.
927-510-4	Hydrocarbon C7-9, n-alcane, is	01-2119475515-33
203-625-9 108-88-3	Toluene	01-2119471310-51

SECTION 16: OTHER INFORMATION

Full text of classification in section 3:		
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging the unborn child.
STOT RE 2 / H373	Specific target organ toxicity (repeated exposure)	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).



Material Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830

Article No.: SX100
Print date: 26.09.2021
Version: 27-0

SX100
Revision date: 26.09.2022
Issue date:

Abbreviations and acronyms:

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

**Data changed compared with the previous version.*