

SAFETY DATA SHEET QT923 - Multiprep

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name QT923 Multiprep

D610-Y0A7-W00G-NJ9R UFI

Synonyms; trade names

IPA, IPS, SEC PROPYL ALCOHOL, ISOPROPYL ALCOHOL, CAFSOL 2, EVERBLEND 15, AL11, IPA LOW ODOUR, ISOPROPANOL, ISOPROPANOL PC SSL, ISOPROPANOL PC SHL, ISOPROPANOL SSL, MX-THINNER HTS 83698, ISOPROPANOL SHELL, ISOPROPANOL EP, ISOPROPANOL (PHARMA), ISOPROPANOL MIN 99.5%, ISOPROPANOL MIN. 99.8%, ISOPROPANOL (IPA), ISOPROPANOL C+, ISOPROPYL ALCOHOL TT-I-735A, ISOPROPANOL PH SHL, ISOPROPANOL BQ, ISOPROPANOL IND, ISOPROPYL ALCOHOL 100%, ISOPROPANOL PC INS, ISOPROPANOL PREM PURE, ISOPROPANOL KML, ISOPROPANOL COSMETIC GRADE, ISOPROPANOL C+ SHL, ISOPROPANOL EXN, ISOPROPANOL BQC, ISOPROPANOL PURE

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EU index number 603-117-00-0 EC number 200-661-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial Solvent In household and cosmetic chemical industry. Pharmaceuticals Chemicals used in the synthesis and / or formulation of industrial products Raw material for cleaning agent Raw material for disinfectants Raw material for photo-chemicals For further information,

see attached Exposure Scenario. Process regulator Processing aid. Solvent.

1.3. Details of the supplier of the safety data sheet

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Not Classified Environmental hazards

2.2. Label elements

EC number 200-661-7

Hazard pictograms





Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Precautionary statements

smoking.

P261 Avoid breathing vapour/ spray.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

SECTION 3: Composition/information on ingredients

3.1. Substances

Product name PROPAN-2-OL

REACH registration number 01-2119457558-25-XXXX

EU index number 603-117-00-0 CAS number 67-63-0 EC number 200-661-7

The data shown are in accordance with the latest EC Directives. Composition comments

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. When breathing is difficult, properly trained

personnel may assist affected person by administering oxygen. Get medical attention.

Ingestion

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues. Wash contaminated clothing before reuse. Skin contact

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort Eye contact

continues.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may irritate throat/respiratory system. Symptoms following overexposure may include the following: Coughing. May cause drowsiness or dizziness. Inhalation

Ingestion Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause

chemical pneumonitis.

Skin contact Product has a defatting effect on skin. Dryness and/or cracking.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness.

Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Suitable extinguishing media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is highly flammable. Vapours are heavier than air and may spread near ground

and travel a considerable distance to a source of ignition and flash back.

Hazardous combustion

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of the following substances: Carbon.

5.3. Advice for firefighters

Protective actions during firefighting

Evacuate area. Stop leak if safe to do so. Avoid the spillage or runoff entering drains, sewers

or watercourses.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Vapours may form explosive mixtures with air. Personal precautions

Avoid contact with skin, eyes and clothing. Keep unnecessary and unprotected personnel away from the spillage. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. For emergency responders

6.2. Environmental precautions

Environmental precautions

Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with inert, damp, non-combustible material. Flush contaminated area with plenty of water. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Avoid breathing gas, fume, vapours or spray. Wash skin thoroughly after handling. Avoid contact with skin, eyes and clothing. Use mechanical ventilation in case of handling which causes formation of vapours. Avoid spilling. Keep away from heat, sparks and open flame.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a well-ventilated place. Keep away from heat, sparks and open flame. Earth container and transfer equipment to eliminate sparks from static electricity. Store at temperatures between 5°C and 25°C. Store away from the following

materials: Acids. Oxidising agents. Alkalis.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit.

DNEL

Industry - Dermal; Long term systemic effects: 888 mg/kg/day Industry - Inhalation; Long term systemic effects: 500 mg/m³ Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m³ Consumer - Oral; Long term systemic effects: 26 mg/kg/day

PNEC - Fresh water; 140.9 mg/l

- marine water; 140.9 mg/l

- Intermittent release; 140.9 mg/l

- STP; 2251 mg/l

- Sediment (Freshwater); 552 mg/kg

- Sediment (Marinewater); 552 mg/kg

- Soil; 28 mg/kg

8.2. Exposure controls

Protective equipment









QT923 Multiprep

Appropriate engineering

controls

Observe any occupational exposure limits for the product or ingredients. Provide explosion proof ventilation for high concentrations. Provide adequate general and local exhaust ventilation. Provide eyewash station and safety shower.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection The most suitable glove should be chosen in consultation with the glove

supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The selected gloves should have a breakthrough time of at least 8 hours. Nitrile rubber. Thickness: > 0.35 mm Butyl rubber. Thickness: > 0.5 mm The selected gloves should have a breakthrough time of at least 4 hours. Chloroprene rubber. Thickness: > 0.4 mm To protect hands from chemicals, gloves should comply with European Standard EN374. Wear apron or protective clothing in case of contact.

Other skin and body

protection

Wash at the end of each work shift and before eating, smoking and using the toilet. Provide eyewash station and safety shower. When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Hygiene measures

If ventilation is inadequate, suitable respiratory protection must be worn. Organic vapour filter. Respiratory protection

Combination filter, type A2/P2. EN 136/140/141/145/143/149

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid. Colour Colourless. Odour Alcoholic.

pΗ No information available.

Melting point -88°C Initial boiling point and range 82 - 83°C 12°C Flash point

Evaporation rate No information available **Evaporation factor** No information available. Flammability (solid, gas) No information available.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 2.0 % Upper flammable/explosive limit: 12 %

Other flammability No information available.

42 hPa @ 20°C Vapour pressure

Vapour density 1.05

0.78-0.79 @ 20°C Relative density

Bulk density No information available.

Solubility(ies) Soluble in water.

Partition coefficient log Pow: 0.05 OECD 107

425°C Auto-ignition temperature

Decomposition Temperature No information available. Viscosity 2.5 mPa s @ 20°C Explosive properties No information available. Explosive under the influence No information available.

of a flame

No information available. Oxidising properties

9.2. Other information

1.377 at 20C Refractive index

Particle size No information available.

Molecular weight 60.1

Volatility No information available. Saturation concentration No information available. No information available. Critical temperature

Volatile organic compound This product contains a maximum VOC content of 100 %.

QT923 Multiprep

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Solvent vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods

of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Alkali metals. Amines. Aluminium. Iron.

10.6. Hazardous decomposition products

Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of the following substances: Carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Acute toxicity oral (LD₅₀

mg/kg)

5,840.0

Rat **Species**

OECD 401 Notes (oral LD₅₀)

QT923 Multiprep

ATE oral (mg/kg) 5.840.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀

mg/kg)

13,900.0

Species Rabbit **OECD 402** Notes (dermal LD₅₀) ATE dermal (mg/kg) 13,900.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV)

10,000.0

Species

Notes (inhalation LC₅₀) LC₅₀ (6h) >10000 ppm, Inhalation, Rat OECD 403

Skin corrosion/irritation

Animal data Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vivo No information available.

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available.

Inhalation May cause respiratory system irritation. Vapours may cause drowsiness and dizziness. Ingestion

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Prolonged contact may cause dryness of the skin.

Skin contact Eye contact Causes serious eye irritation.

Kidneys Liver Target organs

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be toxic to aquatic organisms.

12.1. Toxicity

Not considered toxic to fish. **Toxicity**

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 48 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic

invertebrateś

EC₅₀, 48 hours: 10000 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 7 days: 1800 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability The substance is readily biodegradable.

Biological oxygen demand 53 %

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: 0.05 OECD 107

12.4. Mobility in soil

Mobility The product is soluble in water.

Surface tension 22.7 mN/m @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Do not puncture or incinerate, even when

empty. Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids may self-ignite after use and should be stored in designated fireproof containers with tight-fitting, self-closing lids.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

General Wear protective clothing as described in Section 8 of this safety data sheet.

14.1. UN number

UN No. (ADR/RID) 1219

UN No. (IMDG) 1219

UN No. (ICAO) 1219

UN No. (ADN) 1219

14.2. UN proper shipping name

Proper shipping name (ADR/RID)

ISOPROPANOL (ISOPROPYL ALCOHOL)

Proper shipping name (IMDG) ISOPROPANOL (ISOPROPYL ALCOHOL) Proper shipping name (ICAO) ISOPROPANOL (ISOPROPYL ALCOHOL) Proper shipping name (ADN) ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es)

ADR/RID class ADR/RID classification code F1 ADR/RID label 3 IMDG class 3 ICAO class/division 3 ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group Ш IMDG packing group Ш Ш ICAO packing group ADN packing group Ш

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

14.6. Special precautions for user

F-E, S-D EmS

ADR transport category 2 **Emergency Action Code** •2YE Hazard Identification Number 33 (ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1.

15.2. Safety, health and environmental regulations/legislation specific for the substance or mixture

QT923 Multiprep

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015. This product may impact SEVESO storage regulations.

Restrictions (Annex XVII This product is/contains a substance that is included in REGULATION (EC) No 1907/2006

(REACH) ANNEX XVII - RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE Regulation 1907/2006)

MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND

Seveso Directive - Control of

ARTICLES. Entry number: 3

major accident hazards

15.3. Chemical safety assessment

A chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways

CAS: Chemical Abstracts Service. DNEL: Derived No Effect Level.

IATA: International Air Transport Association. IMDG: International Maritime Dangerous Goods.

Kow: Octanol-water partition coefficient.

LC₅₀: Lethal Concentration to 50 % of a test population.

LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose). PBT: Persistent, Bioaccumulative and Toxic substance.

PNEC: Predicted No Effect Concentration.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail

vPvB: Very Persistent and Very Bioaccumulative. IARC: International Agency for Research on Cancer.

MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.

cATpE: Converted Acute Toxicity Point Estimate. BCF: Bioconcentration Factor.

BOD: Biochemical Oxygen Demand.

EC₅₀: 50% of maximal Effective Concentration.

LOAEC: Lowest Observed Adverse Effect Concentration.
LOAEL: Lowest Observed Adverse Effect Level.
NOAEC: No Observed Adverse Effect Concentration.
NOAEL: No Observed Adverse Effect Level.
NOEC: No Observed Effect Concentration.
LOEC: Lowest Observed Effect Concentration.
DMEL: Derived Minimal Effect Level.
El 50: Exposure Limit 50

EL50: Exposure Limit 50 hPa: Hectopascal

LL50: Lethal Loading fifty

OECD: Organisation for Economic Co-operation and Development

POW: Octanol-water partition coefficient

SCBA: self-contained breathing apparatus

Classification abbreviations and acronyms

STP: Sewage Treatment Plant VOC: Volatile Organic Compounds

Key literature references and

sources for data

Acute Tox. = Acute toxicity

Aguatic Acute = Hazardous to the aguatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Supplier's information.

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 22/04/2022 Version number 6.000

Supersedes date 03/03/2022

SDS number 461

QT923 Multiprep

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Signature Lisa Bland

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Exposure scenario Manufacture of substance - Industrial

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Manufacture of substance - Industrial

Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities. Process scope

Main sector SU3 Industrial uses

SU8 Manufacture of bulk, large-scale chemicals (including petroleum products) SU9 Manufacture of fine chemicals Sector of use

Environment

Environmental release

category Worker

ERC1 Manufacture of the substance

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2 Chemical production or refinery in closed continuous process with occasional Process category

controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with

occasional controlled exposure or processes with equivalent containment condition PROC4 Chemical production where opportunity for exposure arises

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC15 Use as laboratory reagent.

Manufacture of substance - Industrial

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Covers concentrations up to 100 %. Concentration details

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system.

Risk management measures

Use suitable eye protection.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management

Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario Use as an intermediate - Industrial

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Use as an intermediate - Industrial

Process scope Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes

recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

Main sector SU3 Industrial uses

SU8 Manufacture of bulk, large-scale chemicals (including petroleum products) SU9 Manufacture of fine chemicals Sector of use

Environment

Environmental release

category

ERC6a Use of intermediate

Worker

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4 Chemical production where opportunity for exposure arises
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Process category

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC15 Use as laboratory reagent.

Use as an intermediate - Industrial

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Covers concentrations up to 100 %. Concentration details

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system.

Risk management measures

Use suitable eye protection.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management

Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario Distribution of substance - Industrial

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Distribution of substance - Industrial

Process scope

Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

Main sector SU3 Industrial uses

SU8 Manufacture of bulk, large-scale chemicals (including petroleum products) SU9 Manufacture of fine chemicals Sector of use

Environment

Environmental release

category

ERC1 Manufacture of the substance
ERC2 Formulation into mixture
ERC3 Formulation into solid matrix
ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
ERC5 Use at industrial site leading to inclusion into/onto article

ERC6a Use of intermediate

ERC7 Use of functional fluid at industrial site

Worker

Distribution of substance - Industrial

Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3 Manufacture or formulation in the chemical invisal of controlled exposure or processes with equivalent conditions occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including

weighing)

PROC15 Use as laboratory reagent.

Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system.

Risk management measures

Use suitable eye protection.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

> Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Formulation & (re)packing of substances and mixtures - Industrial

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Formulation & (re)packing of substances and mixtures - Industrial

Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tabletting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. Process scope

Main sector SU3 Industrial uses

Sector of use SU10 Formulation [mixing] of preparations and/or re-packaging

Environment

Environmental release

category

Worker

ERC2 Formulation into mixture

Formulation & (re)packing of substances and mixtures - Industrial

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Process category

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
PROC14 Tabletting, compression, extrusion, pelletisation, granulation

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system

prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system.

Risk management measures

Use suitable eye protection.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

> Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels

Exposure scenario Uses in Coatings - Industrial

Identification

Product name QT923 Multiprep

01-2119457558-25-XXXX **REACH** registration number

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Uses in Coatings - Industrial

Process scope

Covers the use in coatings (paints, inks, adhesives, etc.), including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

Main sector SU3 Industrial uses

Environment

Environmental release

category

Worker

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

Uses in Coatings - Industrial

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional Process category

controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises
PROC5 Mixing or blending in batch processes
PROC7 Industrial spraying
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing PROC13 Treatment of articles by dipping and pouring.

PROC15 Use as laboratory reagent.

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Ventilation rate Manual spraying Provide a good standard of controlled ventilation (10 to 15 air changes per

hour).

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system

prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system. PROC7 Industrial

spraying Carry out in a vented booth or extracted enclosure.

Risk management measures

Use suitable eye protection.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Used ECETOC TRA model. Assessment method

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario Use in Cleaning Agents - Industrial

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Use in Cleaning Agents - Industrial

Covers the use as a component of cleaning products, including transfer from storage, pouring/unloading from drums or containers and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, Process scope

automated and by hand), related equipment cleaning and maintenance.

Main sector SU3 Industrial uses

Environment

Environmental release

category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

Worker

PROC1 Chemical production or refinery in closed process without likelihood of exposure or Process category

processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional

controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with

occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring.

Use in Cleaning Agents - Industrial

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Covers concentrations up to 100 %. Concentration details

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Ventilation rate Cleaning with high-pressure washers Provide a good standard of controlled ventilation (10 to

15 air changes per hour).

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system.

Risk management measures

Use suitable eye protection.

Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Used ECETOC TRA model. Assessment method

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario Lubricants - Industrial

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Lubricants - Industrial

Covers the use of formulated lubricants in closed and open systems, including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes. Process scope

Main sector SU3 Industrial uses

Environment

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC7 Use of functional fluid at industrial site Environmental release

category

Worker

Lubricants - Industrial

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional Process category

controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including

weighing)

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring.

PROC17 Lubrication at high energy conditions in metal working operations PROC18 General greasing/lubrication at high kinetic energy conditions

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Covers concentrations up to 100 %. Concentration details

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system

prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system. Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Provide extract ventilation to points where emissions occur.

Risk management measures

Use suitable eye protection.

Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Used ECETOC TRA model. Assessment method

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

26/74

Exposure scenario Metal working fluids / rolling oils - Industrial

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Metal working fluids / rolling oils - Industrial

Process scope

Covers the use in formulated MWFs/rolling oils, including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.

Main sector SU3 Industrial uses

Environment

Environmental release

category

Worker

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

Metal working fluids / rolling oils - Industrial

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional Process category

controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises
PROC5 Mixing or blending in batch processes
PROC7 Industrial spraying
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including

weighing)

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring.

PROC17 Lubrication at high energy conditions in metal working operations

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Covers concentrations up to 100 %. Concentration details

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system

prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system. Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at

openings.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures Automate activity where possible.

Risk management measures

Use suitable eye protection.

Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels

Exposure scenario

Use as binders and release agents - Industrial

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Qualitape UK Ltd Supplier

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Use as binders and release agents - Industrial

Process scope

Covers the use as binders and release agents, including material transfers, mixing, application (including spraying and brushing), mould forming and casting and handling of

waste.

Main sector SU3 Industrial uses

Environment

Environmental release

category Worker

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

PROC1 Chemical production or refinery in closed process without likelihood of exposure or Process category

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3 Manufacture or formulation in the chemical industry in closed batch processes with

PROC3 Manufacture of ormination in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4 Chemical production where opportunity for exposure arises PROC6 Calendering operations.
PROC7 Industrial spraying PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC10 Roller application or brushing

PROC14 Tabletting, compression, extrusion, pelletisation, granulation

2. Conditions of use affecting exposure (Industrial - Environment 1)

Use as binders and release agents - Industrial

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures

Avoid direct eye contact with product, also via contamination on hands. Drain down system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system. Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Manual spraying Carry out in a vented booth or extracted enclosure.

Organisational measures to prevent/limit releases, dispersion and exposure

Automate activity where possible. Organisational measures

Risk management measures

Use suitable eye protection.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

> Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario Functional Fluids - Industrial

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Functional Fluids - Industrial

Process scope

Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in industrial equipment, including maintenance and related material transfers.

Main sector SU3 Industrial uses

Environment

Environmental release

category

ERC7 Use of functional fluid at industrial site

Worker

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional Process category

controlled exposure or processes with equivalent containment conditions

PROC4 Chemical production where opportunity for exposure arises PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including

weighing)

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

Conditions of use affecting exposure (Workers - Health 1)

Functional Fluids - Industrial

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures Use drum pumps or carefully pour from container.

Risk management measures

Use suitable eye protection.

Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

Exposure estimation (Health 1)

Used ECETOC TRA model. Assessment method

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Use in laboratories - Industrial

Identification

Product name QT923. Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Use in laboratories - Industrial

Process scope Use of the substance within laboratory settings, including material transfers and equipment

cleaning.

Main sector SU3 Industrial uses

Environment

Environmental release

ERC2 Formulation into mixture category

Worker

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

PROC10 Roller application or brushing PROC15 Use as laboratory reagent. Process category

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Use in laboratories - Industrial

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands.

Risk management measures

Use suitable eye protection.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario

Water treatment chemicals - Industrial

Identification

QT923 Multiprep Product name

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Water treatment chemicals - Industrial

Process scope Covers the use of the substance for the treatment of water at industrial facilities in open and

closed systems.

Main sector SU3 Industrial uses

Environment

Environmental release

category

ERC3 Formulation into solid matrix

Worker

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or

processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional

controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with

occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC13 Treatment of articles by dipping and pouring.

2. Conditions of use affecting exposure (Industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Workers - Health 1)

Water treatment chemicals - Industrial

Product characteristics

Liquid, vapour pressure 0.5 - 10 kPa at STP Physical state

Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Drain down system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Store substance within a closed system.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures Use drum pumps or carefully pour from container.

Risk management measures

Use suitable eye protection.

Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

Exposure estimation (Health 1)

Used ECETOC TRA model. Assessment method

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure scenario Use in Coatings - Professional

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Use in Coatings - Professional

Process scope

Covers the use in coatings (paints, inks, adhesives, etc.), including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods and film formation) and equipment cleaning, maintenance and associated laboratory activities.

Main sector SU22 Professional uses

Environment

Environmental release ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article,

indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Worker

category

Use in Coatings - Professional

Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4 Chemical production where opportunity for exposure arises

PROC5 Mixing or blending in batch processes

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring. PROC15 Use as laboratory reagent.

PROC19 Manual activities involving hand contact

Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Store substance

within a closed system. Manual spraying Indoor. Carry out in a vented booth or extracted

enclosure.

Risk management measures

Use suitable eye protection.

Manual spraying

Wear a respirator conforming to EN140 with Type A filter or better.

Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Used ECETOC TRA model. Assessment method

> Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario Use in Cleaning Agents - Professional

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Use in Cleaning Agents - Professional

Covers the use as a component of cleaning products, including pouring/unloading from drums or containers and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand). Process scope

SU22 Professional uses Main sector

Environment

Environmental release

category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article,

indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Worker

Use in Cleaning Agents - Professional

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Process category

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with

occasional controlled exposure or processes with equivalent containment condition PROC4 Chemical production where opportunity for exposure arises PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring. PROC15 Use as laboratory reagent.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP Covers concentrations up to 100 %. Concentration details

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Ventilation rate Spraying Indoor. Provide a good standard of controlled ventilation (10 to 15 air changes per

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eve contact with product, also via contamination on hands. Store substance

within a closed system.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures Spraying Outdoor. Avoid carrying out activities involving exposure for more than 15 minutes.

Limit the substance content in the product to 1%.

Risk management measures

Use suitable eye protection.

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

Exposure estimation (Health 1)

Used ECETOC TRA model. Assessment method

> Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Revision date: 22/04/2022

Exposure scenario Lubricants - Professional

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Lubricants - Professional

Process scope

Covers the use of formulated lubricants in closed and open systems, including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.

Main sector SU22 Professional uses

Environment

Environmental release ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, category

indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article,

outdoor)
ERC9a Widespread use of functional fluid (indoor)
ERC9b Widespread use of functional fluid (outdoor)

Worker

Lubricants - Professional

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional Process category

controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including

weighing)
PROC10 Roller application or brushing
PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring.

PROC17 Lubrication at high energy conditions in metal working operations PROC18 General greasing/lubrication at high kinetic energy conditions PROC20 Use of functional fluids in small devices

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Covers concentrations up to 100 %. Concentration details

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Minimise exposure by

partial enclosure of the operation or equipment and provide extract ventilation at openings. Provide extract ventilation to emission points when contact with warm (> 50°C) lubricant is

likely. Store substance within a closed system.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures Avoid carrying out activities involving exposure for more than 4 hours. Allow time for product

to drain from workpiece. Retain drain-downs in sealed storage pending disposal or for

subsequent recycle.

Risk management measures

Use suitable eye protection.

If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A/P2 filter or better.

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management

Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario Metal working fluids / rolling oils - Professional

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Metal working fluids / rolling oils - Professional

Covers the use in formulated MWFs, including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles and disposal of waste oils. Process scope

Main sector SU22 Professional uses

Environment

Environmental release

category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
ERÇ8d Widespread use of non-reactive processing aid (no inclusion into or onto article,

outdoor)

Worker

Metal working fluids / rolling oils - Professional

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional Process category

controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC5 Mixing or blending in batch processes PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including

weighing)
PROC10 Roller application or brushing
PROC11 Non industrial spraying

Covers concentrations up to 100 %.

PROC13 Treatment of articles by dipping and pouring.

PROC17 Lubrication at high energy conditions in metal working operations

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Concentration details

Liquid, vapour pressure 0.5 - 10 kPa at STP Physical state

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Minimise exposure by

partial enclosure of the operation or equipment and provide extract ventilation at openings. Spraying Carry out in a vented booth or extracted enclosure. Store substance within a closed system. Bulk transfers Clear transfer lines prior to de-coupling.

Organisational measures to prevent/limit releases, dispersion and exposure

Avoid carrying out activities involving exposure for more than 4 hours. Allow time for product to drain from workpiece. Retain drain-downs in sealed storage pending disposal or for Organisational measures

subsequent recycle.

Risk management measures

Use suitable eye protection.

If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A/P2 filter or better.

Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management

Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario

Use as binders and release agents - Professional

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Use as binders and release agents - Professional

Process scope Covers the use as binders and release agents, including material transfers, mixing,

application by spraying, brushing and handling of waste.

Main sector SU22 Professional uses

Environment

Environmental release

category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article,

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article,

outdoor)

Worker

Process category PROC1 Chemical production or refinery in closed process without likelihood of exposure or

processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional

controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with

occasional controlled exposure or processes with equivalent containment condition PROC4 Chemical production where opportunity for exposure arises

PROC6 Calendering operations.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC14 Tabletting, compression, extrusion, pelletisation, granulation

Use as binders and release agents - Professional

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Covers concentrations up to 100 %. Concentration details

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Minimise exposure by

partial enclosure of the operation or equipment and provide extract ventilation at openings. Spraying Carry out in a vented booth or extracted enclosure. Store substance within a closed

Organisational measures to prevent/limit releases, dispersion and exposure

Avoid carrying out activities involving exposure for more than 4 hours. Allow time for product Organisational measures

to drain from workpiece. Retain drain-downs in sealed storage pending disposal or for

subsequent recycle.

Risk management measures

Use suitable eye protection.

If above technical/organisational control measures are not feasible, then adopt following PPE:

Wear a respirator conforming to EN140 with Type A/P2 filter or better.

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario Use in Agrochemicals - Professional

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Use in Agrochemicals - Professional

Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging, including equipment clean-downs and disposal. Process scope

Main sector SU22 Professional uses

Environment

Environmental release

category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article,

indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article,

outdoor)

Worker

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Process category

PROC4 Chemical production where opportunity for exposure arises

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Use in Agrochemicals - Professional

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Spraying/fogging by

machine application Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of > 20. Store substance within a closed system.

Organisational measures to prevent/limit releases, dispersion and exposure

Avoid carrying out activities involving exposure for more than 4 hours. Spraying/fogging by manual application Limit the substance content in the product to 25%. Retain drain-downs in Organisational measures

sealed storage pending disposal or for subsequent recycle.

Risk management measures

Use suitable eye protection.

If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A/P2 filter or better.

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario Functional Fluids - Professional

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

I. Title of exposure scenario

Main title Functional Fluids - Professional

Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in professional equipment, including maintenance and related material Process scope

Main sector SU22 Professional uses

Environment

Environmental release

category

ERC9a Widespread use of functional fluid (indoor) ERC9b Widespread use of functional fluid (outdoor)

Worker

Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including

weighing)

PROC20 Use of functional fluids in small devices

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Functional Fluids - Professional

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently. Temperature

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Store substance

within a closed system.

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures Retain drain-downs in sealed storage pending disposal or for subsequent recycle. Carefully

pour from containers.

Risk management measures

Use suitable eye protection.

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario

De-icing and anti-icing applications - Professional

Identification

QT923 Multiprep Product name

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Qualitape UK Ltd Supplier

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title De-icing and anti-icing applications - Professional

Process scope Ice prevention and de-icing of vehicles, aircraft and other equipment by spraying.

SU22 Professional uses Main sector

Environment

Environmental release

category

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article,

outdoor)

Worker

Process category PROC1 Chemical production or refinery in closed process without likelihood of exposure or

processes with equivalent containment conditions
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

facilities
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC11 Non industrial spraying

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP Concentration details Covers concentrations up to 100 %.

Frequency and duration of use

De-icing and anti-icing applications - Professional

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Bulk transfers Clear transfer lines prior to de-coupling.

Organisational measures to prevent/limit releases, dispersion and exposure

Avoid carrying out activities involving exposure for more than 1 hour. Spraying/fogging by machine application Ensure operation is undertaken outdoors. Stay upwind/keep distance Organisational measures

Risk management measures

Use suitable eye protection.

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario Use in laboratories - Professional

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Use in laboratories - Professional

Process scope Use of small quantities within laboratory settings, including material transfers and equipment

cleaning.

Main sector SU22 Professional uses

Environment

Environmental release

category

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Worker

PROC10 Roller application or brushing PROC15 Use as laboratory reagent. Process category

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Covers concentrations up to 100 %. Concentration details

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Use in laboratories - Professional

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands.

Risk management measures

Use suitable eye protection.

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario

Water treatment chemicals - Professional

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Water treatment chemicals - Professional

Process scope Covers the use of the substance for the treatment of water in open and closed systems.

SU22 Professional uses Main sector

Environment

Environmental release

category Worker

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or

processes with equivalent containment conditions
PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC13 Treatment of articles by dipping and pouring.

2. Conditions of use affecting exposure (Workers - Health 1)

Product characteristics

Physical state Liquid, vapour pressure 0.5 - 10 kPa at STP

Concentration details Covers concentrations up to 100 %.

Water treatment chemicals - Professional

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently).

Other given operational conditions affecting workers exposure

Temperature Assumes use at not more than 20°C above ambient temperature, unless stated differently.

Assumes a good basic standard of occupational hygiene is implemented.

Technical conditions and measures at process level (source) to prevent release

Technical protective measures Avoid direct eye contact with product, also via contamination on hands. Bulk transfers Clear transfer lines prior to de-coupling. Drum/batch transfers Use drum pumps or carefully pour

from container

Organisational measures to prevent/limit releases, dispersion and exposure

Organisational measures Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Risk management measures

Use suitable eye protection.

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management

Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario

Use in Coatings - Consumer

Identification

QT923 Multiprep Product name

01-2119457558-25-XXXX **REACH** registration number

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Use in Coatings - Consumer

Covers the use in coatings (paints, inks, adhesives, etc.), including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning. Process scope

Product category PC1 Adhesives, sealants.

PC4 Anti-freeze and de-icing products.
PC8 Biocidal products
PC9a Coatings and paints, thinners, paint removers.
PC9b Fillers, putties, plasters, modelling clay.

PC9c Finger paints.

PC15 Non-metal-surface treatment products. PC18 Ink and toners.

PC23 Leather treatment products

PC24 Lubricants, greases and release products. PC31 Polishes and wax blends.

PC34 Textile dyes and impregnating products

Main sector SU21 Consumer uses

Environment

Environmental release

category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article,

indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article,

outdoor)

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Use in Coatings - Consumer

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Product characteristics

Physical state Liquid, vapour pressure > 10 Pa (STP)

Concentration details Covers concentrations up to 50 %. Unless otherwise stated.

> PC1 Adhesives, sealants. Covers concentrations up to 30 %. PC8_2 Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) Covers concentrations up to 5 %. PC8_3 Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) Covers concentrations up to 15 %. PC9a_2 Solvent-rich, high-solid, water-borne paint Covers concentrations up to 27.5 %. PC9b_1 Fillers and putty PC9b_2 Plasters and floor equalisers Covers concentrations up to 2 %. PC9b_3 Modelling clay Covers concentrations up to 10 %. PC15 Non-metal-surface treatment products. Solvent-rich paint Covers concentrations up to 27.5 . PC18 Ink and toners. Covers concentrations up to 10 %. PC24 Lubricants, greases and release products. PC24_1 Liquids Covers concentrations up to 100 %. PC24 Lubricants, greases and release products. PC24_2 Pastes Covers concentrations up to 20 %.

Amounts used

Frequency and duration of use

PC9b_2 Plasters and floor equalisers

For each use event, covers use amounts up to 13,800 g. PC1_2 Glues DIY-use (carpet glue, tile glue, wood parquet glue)

For each use event, covers use amounts up to 6,390 g.

For each use event, covers use amounts up to 2,200 g. PC4_2 Pouring into radiator

FC4_2 Fouring into radiator

For each use event, covers use amounts up to 2,000 g.

PC9a_2 Solvent-rich, high-solid, water-borne paint

PC9a_3 Aerosol spray can

PC9a_4 Removers (paint-, glue-, wallpaper-, sealant-remover)

PC31_1 Polishes, wax/cream (floor, furniture, shoes)

PC34 Textile dyes and impregnating products

For each use event, covers use amounts up to 1,000 g.

PC1_3 Glue from spray

PC1_4 Sealants

PC8 Biocidal products

PC9b_1 Fillers and putty

PC18 Ink and toners.

PC31_2 Polishes, spray (furniture, shoes) PC24_2 Pastes

PC24_3 Sprays

For each use event, covers use amounts up to 100 g. PC4_1 Washing car window PC4_3 Look delicer

PC9b_3 Modelling clay

PC9c Finger paints

For each use event, covers use amounts up to 10 g.

Covers use up to 1 time per day. Covers use up to 365 days/year. Unless otherwise stated.

Use in Coatings - Consumer

PC8 Biocidal products Covers use up to 128 days/year. PC31_1 Polishes, wax/cream (floor, furniture, shoes) Covers use up to 29 days/year. PC9b_1 Fillers and putty PC9b_2 Plasters and floor equalisers Covers use up to 12 days/year. PC24 Lubricants, greases and release products. PC24_2 Pastes Covers use up to 10 days/year. PC31_2 Polishes, spray (furniture, shoes) Covers use up to 8 days/year. PC1_3 Glue from spray PC9a_2 Solvent-rich, high-solid, water-borne paint PC24 Lubricants, greases and release products. PC24_3 Sprays Covers use up to 6 days/year. PC24 Lubricants, greases and release products. PC24_1 Liquids Covers use up to 4 days/year. PC9a_4 Removers (paint-, glue-, wallpaper-, sealant-remover). Covers use up to 3 days/year. PC9a_3 Aerosol spray can Covers use up to 2 days/year. PC1_2 Glues DIY-use (carpet glue, tile glue, wood parquet glue) Covers use up to 1 days/year.

Human factors not influenced by risk management

Potentially exposed body parts

PC1_1 Glues, hobby use PC1_3 Glue from spray PC1_4 Sealants PC9b_1 Fillers and putty Covers skin contact area up to 35.73 cm². PC1_2 Glues DIY-use (carpet glue, tile glue, wood parquet glue) Covers skin contact area up to 110 cm². PC4_2 Pouring into radiator PC8 Biocidal products PC8_3 Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) PC9a_2 Solvent-rich, high-solid, water-borne paint PC31 Polishes and wax blends. PC24_3 Sprays Covers skin contact area up to 430 cm². PC4_3 Lock de-icer Covers skin contact area up to 214.4 cm². PC8 Biocidal products PC8_2 Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) PC9a_4 Removers (paint-, glue-, wallpaper-, sealant-remover) PC9b_2 Plasters and floor equalisers Covers skin contact area up to 857.5 cm². PC9b_3 Modelling clay PC9c Finger paints. Covers skin contact area up to 254.4 cm². PC18 Ink and toners. Covers skin contact area up to 468 cm².

Other given operational conditions affecting Non-industrial exposure

Temperature Assumes activities are at ambient temperature (unless stated differently).

Room size Covers use in room size of 20 m³. Unless otherwise stated.

Ventilation rate Covers use under typical household ventilation., or: Covers use in a one car garage (34 m³)

under typical ventilátion.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method

Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario Use in Cleaning Agents - Consumer

Identification

QT923 Multiprep Product name

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Qualitape UK Ltd Supplier

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Use in Cleaning Agents - Consumer

Process scope Covers general exposures to consumers arising from the use of household products sold as

washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.

Product category PC3 Air care products.

PC4 Anti-freeze and de-icing products.

PC8 Biocidal products

PC9a Coatings and paints, thinners, paint removers. PC24 Lubricants, greases and release products.

PC35 Washing and cleaning products

PC38 Welding and soldering products, flux products

Main sector SU21 Consumer uses

Environment

Environmental release

category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article,

indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article,

outdoor)

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Product characteristics

Use in Cleaning Agents - Consumer

Physical state Liquid, vapour pressure > 10 Pa (STP)

Concentration details Covers concentrations up to 50 %. Unless otherwise stated.

PC9a_2 Solvent-rich, high-solid, water-borne paint Covers concentrations up to 27.5 %. PC8_2 Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) PC24 Lubricants, greases and release products. PC24_1 Liquids Covers concentrations up to 100 %. PC24 Lubricants, greases and release products. PC24_2 Pastes Covers concentrations up to 20 %. PC35 Washing and cleaning products Covers concentrations up to 20 %.

products Covers concentrations up to 70 %.

Amounts used

PC24 Lubricants, greases and release products. PC24_1 Liquids

For each use event, covers use amounts up to 2,200 g. PC4 Anti-freeze and de-icing products.

PC4 2 Pouring into radiator

For each use event, covers use amounts up to 2,000 g. PC9a_2 Solvent-rich, high-solid, water-borne paint PC9a_3 Aerosol spray can

PC9a_4 Removers (paint-, glue-, wallpaper-, sealant-remover)

For each use event, covers use amounts up to 1,000 g.

PC8 Biocidal products

PC24 Lubricants, greases and release products.

PC24_2 Pastes PC24_3 Sprays

PC35 Washing and cleaning products

PC38 Welding and soldering products, flux products For each use event, covers use amounts up to 100 g.

PC4_3 Lock de-icer

For each use event, covers use amounts up to 4 g.

PC3 Air care products.

Frequency and duration of use

For each use event, covers use amounts up to 1 g.

Covers use up to 365 days/year. Unless otherwise stated. Covers use up to 1 time per day.

Unless otherwise stated.

PC3_1 Air care, instant action (aerosol sprays)
PC3_2 Air care, continuous action (solid and liquid)
Covers use up to 4 times per day.

PC8_2 Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) PC8_3 Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) PC35 Washing and cleaning products Covers use up to 128 days/year. PC9a_2 Solvent-rich, high-solid, water-borne paint PC24 Lubricants, greases and release products. PC24_3 Sprays Covers use up to 6 days/year. PC9a_3 Aerosol spray can Covers use up to 2 days/year. PC9a_4 Removers (paint-, glue-, wallpaper-, sealant-remover). Covers use up to 3 days/year. PC24 Lubricants, greases and release products. PC24_1 Liquids Covers use up to 4 days/year. PC24 Lubricants, greases and release products. PC24_2 Pastes Covers use up to 10 days/year.

Human factors not influenced by risk management

Revision date: 22/04/2022

Use in Cleaning Agents - Consumer

Potentially exposed body

parts

Covers skin contact area up to 857.5 cm². Unless otherwise stated. PC24 Lubricants, greases and release products. PC24_1 Liquids PC24_2 Pastes Covers skin contact area up to 468 cm². PC3_1 Air care, instant action (aerosol sprays) PC4 Anti-freeze and de-icing products. PC4_2 Pouring into radiator PC8 Biocidal products PC8_3 Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) PC9a_2 Solvent-rich, high-solid, waterborne paint PC24 Lubricants, greases and release products. PC24_3 Sprays PC35 Washing and cleaning products PC8_3 Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) Covers skin contact area up to 428 cm². PC4 Anti-freeze and de-icing products. PC4_3 Lock de-icer Covers skin contact area up to 214.4 cm². PC3_2 Air care, continuous action (solid and liquid) Covers skin contact area up to 35.70 cm².

Other given operational conditions affecting Non-industrial exposure

Temperature Assumes activities are at ambient temperature (unless stated differently).

Room size Covers use in room size of 20 m³. Unless otherwise stated.

Ventilation rate Covers use under typical household ventilation., or: Covers use in a one car garage (34 m³)

under typical ventilátion.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Revision date: 22/04/2022

Exposure scenario Lubricants - Consumer

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Lubricants - Consumer

Covers the consumer use of formulated lubricants in closed and open systems, including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil. Process scope

Product category PC1 Adhesives, sealants.

PC24 Lubricants, greases and release products. PC31 Polishes and wax blends.

SU21 Consumer uses Main sector

Environment

Environmental release

category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article,

indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article,

outdoor)

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Product characteristics

Liquid, vapour pressure > 10 Pa (STP) Physical state

Concentration details Covers concentrations up to 30 %. Unless otherwise stated.

Lubricants - Consumer

PC24 Lubricants, greases and release products. PC24_1 Liquids Covers concentrations up to 100 %. PC24 Lubricants, greases and release products. PC24_3 Sprays PC31 Polishes and wax blends. Covers concentrations up to 50 %. PC24 Lubricants, greases and release products. PC24_2 Pastes Covers concentrations up to 20 %.

Amounts used

PC1_2 Glues DIY-use (carpet glue, tile glue, wood parquet glue) For each use event, covers use amounts up to 6,390 g.

PC24 Lubricants, greases and release products.

PC24_1 Liquids

For each use event, covers use amounts up to 2,200 g. PC31_1 Polishes, wax/cream (floor, furniture, shoes) For each use event, covers use amounts up to 142 g. PC1_3 Glue from spray

PC1 4 Sealants

PC24 Lubricants, greases and release products. PC24_2 Pastes

PC24_3 Sprays

PC31_2 Polishes, spray (furniture, shoes)

For each use event, covers use amounts up to 100 g. PC1_1 Glues, hobby use

Frequency and duration of use For each use event, covers use amounts up to 9 g.

Covers use up to 1 time per day.

PC1_1 Glues, hobby use PC1_4 Sealants Covers use up to 365 days/year. PC31_1 Polishes, wax/cream (floor, furniture, shoes) Covers use up to 29 days/year. PC24 Lubricants, greases and release products. PC24_2 Pastes Covers use up to 10 days/year. PC31_2 Polishes, spray (furniture, shoes) Covers use up to 8 days/year. PC1_3 Glue from spray PC24 Lubricants, greases and release products. PC24_3 Sprays Covers use up to 6 days/year. PC24 Lubricants, greases and release products. PC24_1 Liquids Covers use up to 4 days/year. PC1_2 Glues DIY-use (carpet glue, tile glue, wood parquet glue) Covers use up to 1 days/year.

Human factors not influenced by risk management

Potentially exposed body

parts

PC24 Lubricants, greases and release products. PC24_1 Liquids PC24_2 Pastes Covers skin contact area up to 468 cm². PC24 Lubricants, greases and release products. PC24_3 Sprays PC31 Polishes and wax blends. Covers skin contact area up to 430 cm². PC1_2 Glues DIY-use (carpet glue, tile glue, wood parquet glue) Covers skin contact area up to 110.00 cm². PC1_1 Glues, hobby use PC1_3 Glue from spray PC1_4 Sealants Covers skin contact area up to 35.70 cm².

Other given operational conditions affecting Non-industrial exposure

Assumes activities are at ambient temperature (unless stated differently). Temperature

Room size Covers use in room size of 20 m3. Unless otherwise stated.

Ventilation rate Covers use under typical household ventilation., or: Covers use in a one car garage (34 m³)

under typical ventilátion.

Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Used ECETOC TRA model. Assessment method

> Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario Use in Agrochemicals - Consumer

Identification

Product name QT923. Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk **CB9 8PA**

1. Title of exposure scenario

Main title Use in Agrochemicals - Consumer

Process scope Covers the consumer use in agrochemicals in liquid and solid forms.

PC12 Lawn and garden preparations (- fertilizers). Product category

PC27 Plant protection products.

Main sector SU21 Consumer uses

Environment

Environmental release

category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article,

indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Product characteristics

Physical state Liquid, vapour pressure > 10 Pa (STP)

Concentration details Covers concentrations up to 50 %. Unless otherwise stated.

Amounts used

Use in Agrochemicals - Consumer

For each use event, covers use amounts up to 50 g.

Frequency and duration of use

For each use event, avoid swallowing amounts more than 0.3 g.

Covers use up to 1 time per day. Covers use up to 365 days/year.

Human factors not influenced by risk management

Potentially exposed body

Covers skin contact area up to 875.5 cm2.

parts

Other given operational conditions affecting Non-industrial exposure

Temperature Assumes activities are at ambient temperature (unless stated differently).

Room size Covers use in room size of 20 m³. Unless otherwise stated.

Ventilation rate Covers use under typical household ventilation.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management

Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario Functional Fluids - Consumer

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0
EC number 200-661-7
EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Functional Fluids - Consumer

Process scope Use of sealed items containing functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.

Product category PC16 Heat transfer fluids.

PC17 Hydraulic fluids.

Main sector SU21 Consumer uses

Environment

Environmental release ERC9a Widespread use of functional fluid (indoor) category ERC9b Widespread use of functional fluid (outdoor)

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Product characteristics

Physical state Liquid, vapour pressure > 10 Pa (STP)

Concentration details Covers concentrations up to 100 %. Unless otherwise stated.

Amounts used

For each use event, covers use amounts up to 2,200 g.

Frequency and duration of use

Functional Fluids - Consumer

Covers use up to 4 days/year.

Covers exposure up to 0.17 hours per event.

Human factors not influenced by risk management

Potentially exposed body

parts

Covers skin contact area up to 468 cm².

Other given operational conditions affecting Non-industrial exposure

Temperature Assumes activities are at ambient temperature (unless stated differently).

Room size Covers use in room size of 20 m3. Unless otherwise stated. Ventilation rate Covers use in a one car garage (34 m³) under typical ventilation.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Used ECETOC TRA model. Assessment method

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario

De-icing and anti-icing applications - Consumer

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title De-icing and anti-icing applications - Consumer Process scope De-icing of vehicles and similar equipment by spraying.

Product category PC4 Anti-freeze and de-icing products.

Main sector SU21 Consumer uses

Environment

Environmental release

category

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article,

outdoor)

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Product characteristics

Liquid, vapour pressure > 10 Pa (STP) Physical state

Concentration details

Covers concentrations up to 40 %. Unless otherwise stated. PC4_1 Washing car window Covers concentrations up to 1 %. PC4_2 Pouring into radiator Covers concentrations up to 10

Amounts used

For each use event, covers use amounts up to 2000 g.

Unless otherwise stated.

De-icing and anti-icing applications - Consumer

PC4_1 Washing car window For each use event, covers use amounts up to 0.5 g. PC4_3 Lock de-icer For each use event, covers use amounts up to 4 g.

Frequency and duration of use

Covers use up to 365 days/year.

PC4_1 Washing car window Covers exposure up to 0.02 hours per event. PC4_2 Pouring into radiator Covers exposure up to 0.17 hours per event. PC4_3 Lock de-icer Covers exposure up to 0.25 hours per event.

Human factors not influenced by risk management

Potentially exposed body parts

Covers skin contact area up to 428 cm². Unless otherwise stated. PC4_3 Lock de-icer Covers

skin contact area up to 214.4 cm².

Other given operational conditions affecting Non-industrial exposure

Temperature Assumes activities are at ambient temperature (unless stated differently).

Ventilation rate Covers use in a one car garage (34 m³) under typical ventilation.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method

Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario

Water treatment chemicals - Consumer

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Water treatment chemicals - Consumer

Process scope Covers the use of the substance for the treatment of water in open and closed systems.

Product category PC36 Water softeners.

PC37 Water treatment chemicals.

Main sector SU21 Consumer uses

Environment

Environmental release ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, category

outdoor)

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Product characteristics

Liquid, vapour pressure > 10 Pa (STP) Physical state

Concentration details Covers concentrations up to 20 %. Unless otherwise stated.

Amounts used

For each use event, covers use amounts up to 10 g. Unless otherwise stated.

Water treatment chemicals - Consumer

Frequency and duration of use

Covers use up to 365 days/year.

Human factors not influenced by risk management

Potentially exposed body

Covers skin contact area up to 6,600 cm². Unless otherwise stated.

Other given operational conditions affecting Non-industrial exposure

Temperature Assumes activities are at ambient temperature (unless stated differently).

Room size Covers use in room size of 20 m³.

3. Exposure estimation (Environment 1)

As no environmental hazard was identified, no environmental-related exposure assessment and risk characterisation was performed.

3. Exposure estimation (Health 1)

Assessment method Used ECETOC TRA model.

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

4. Guidance to check compliance with the exposure scenario (Health 1)

Exposure scenario Other Consumer Uses

Identification

Product name QT923 Multiprep

REACH registration number 01-2119457558-25-XXXX

CAS number 67-63-0 EC number 200-661-7 EU index number 603-117-00-0

Supplier Qualitape UK Ltd

Unit 1 Sarah Court

Haverhill Suffolk CB9 8PA

1. Title of exposure scenario

Main title Other Consumer Uses

Process scope

Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: for cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation.

Product category PC28 Perfumes, fragrances.

PC39 Cosmetics, personal care.

Main sector SU21 Consumer uses

Environment

Environmental release

category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article,

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

2. Conditions of use affecting exposure (Non-industrial - Environment 1)

Product characteristics

Not regarded as dangerous for the environment. No exposure scenario required.

2. Conditions of use affecting exposure (Non-industrial - Health 1)

Product characteristics

In accordance to the Article 14 (5b) of the REACH Regulation (EC) No 1907/2006, exposure estimation and risk characterisation for human health does not need to be performed for end uses in cosmetic products within the scope of Directive 76/768/EEC.

Other Consumer Uses

3. Exposure estimation (Environment 1)

3. Exposure estimation (Health 1)

No exposure assessment presented for human health.

4. Guidance to check compliance with the exposure scenario (Health 1)