

LOCKFAST R20

Page: 1

Compilation date: 27/02/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LOCKFAST R20

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Cyanotec Ltd

Bay 2 Building 62 Third Avenue Pensnett Trading Estate Kingswinford DY6 7XT Tel: >>>

Email: tim@cyanotec.com

1.4. Emergency telephone number

Emergency tel: 0845 6183120

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP:	Xn: R20; Xi: R36/37/38; Sens.: R43; N: R51/53
Classification under CLP:	STOT SE 3: H335; Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin
	Irrit. 2: H315; Skin Sens. 1A: H317; -: EUH208
Most important adverse effects:	Harmful by inhalation. Irritating to eyes, respiratory system and skin. May cause
	sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse
	effects in the aquatic environment.

2.2. Label elements

Label elements under CLP:	
Hazard statements:	EUH208: Contains hydroquinone monomethyl ether. May produce an allergic reaction.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H332: Harmful if inhaled.
	H335: May cause respiratory irritation.
	H411: Toxic to aquatic life with long lasting effects.
Signal words:	Warning

LOCKFAST R20

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental



Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor if you feel unwell.

P321: Specific treatment (see instructions on this label).

Label elements under CHIP:

Hazard symbols: Harmful.

Dangerous for the environment.



Risk phrases:	R20: Harmful by inhalation.
	R36/37/38: Irritating to eyes, respiratory system and skin.
	R43: May cause sensitisation by skin contact.
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
Safety phrases:	S24: Avoid contact with skin.
	S37: Wear suitable gloves.
	S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
Precautionary phrases:	Contains hydroquinone monomethyl ether, 1-acetyl-2-phenylhydrazine. May produce an
	allergic reaction.
2.3. Other hazards	

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

Page: 2

LOCKFAST R20

Page: 3

BISPHENOL A ETHOXYLATE DIMETHACRYLATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	41637-38-1	Xi: R36/37/38; Sens.: R43	Skin Irrit. 2: H315; Skin Sens. 1A: H317; Eye Irrit. 2: H319; STOT SE 3: H335	50-70%

1,1'-(METHYLENEDI-P-PHENYLENE) BISMALEIMIDE

- 13676-54-5 T: R23; Xi: R36/37/38; Sens.: R43; N: R50/53	Skin Sens. 1A: H317; Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335; Acute Tox. 3: H331; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	10-30%
--------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------	--------

2-CARBOXYETHYL ACRYLATE

246	6-359-9	24615-84-7	C: R34	Acute Tox. 4: H302; Aquatic Acute 1:	1-10%
				H400; Eye Dam. 1: H318; STOT SE 3:	
				H335; Aquatic Chronic 3: H412	

CUMENE HYDROPEROXIDE

201-254-7	80-15-9		Org. Perox. EF: H242; Acute Tox. 3:	1-10%
		Xn: R48/20/22; N: R51/53	H331; Acute Tox. 4: H312; Acute Tox. 4:	
			H302; STOT RE 2: H373; Skin Corr.	
			1B: H314	

N,N-DIMETHYL-P-TOLUIDINE - REACH registered number(s): 01-2119937766-23

202-805-4	99-97-8	T: R23/24/25; Xn: R33; -: R52/53	Acute Tox. 3: H331; Acute Tox. 3: H311;	<1%
			Acute Tox. 3: H301; STOT RE 2: H373;	
			Aquatic Chronic 3: H412	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

- **Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.
- Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

LOCKFAST R20

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Polyethylene. Do not use steel containers.

LOCKFAST R20

Page: 5

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. The floor of the storage room must be
	impermeable to prevent the escape of liquids.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic phy	sical and chemical properties		
State:	Liquid		
Colour:	•		
Odour:	Characteristic odour		
Evaporation rate:	No data available.		
-	No data available.		
Solubility in water:			
Also soluble in:	Most organic solvents.		
Viscosity:	Highly viscous		
Viscosity test method:	Cone and Plate @ 25°C (CPs)		
Boiling point/range°C:	>35 Me	Iting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	>93 Part.coe	eff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	1.05	pH:	Not applicable.
VOC g/I:	No data available.		
9.2. Other information			

Other information: No data available.

Section 10: Stability and reactivity

LOCKFAST R20

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

CUMENE HYDROPEROXIDE

ORL	MUS	LDLO	5	gm/kg
ORL	RAT	LD50	382	mg/kg
SCU	RAT	LD50	382	mg/kg

N,N-DIMETHYL-P-TOLUIDINE

IPR MUS LD50	212 mg/kg
--------------	-----------

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH	Hazardous: calculated
Irritation	OPT INH DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

LOCKFAST R20

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

LOCKFAST R20

Page: 8

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH208: Contains <name of="" sensitising="" substance="">. May produce an allergic reaction.</name>
	H242: Heating may cause a fire.
	H301: Toxic if swallowed.
	H302: Harmful if swallowed.
	H311: Toxic in contact with skin.
	H312: Harmful in contact with skin.
	H314: Causes severe skin burns and eye damage.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H318: Causes serious eye damage.
	H319: Causes serious eye irritation.
	H331: Toxic if inhaled.
	H332: Harmful if inhaled.
	H335: May cause respiratory irritation.
	H373: May cause damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through</or>
	prolonged or repeated exposure <state conclusively="" exposure="" if="" is="" it="" of="" proven="" route="" th="" that<=""></state>
	no other routes of exposure cause the hazard>.
	H400: Very toxic to aquatic life.
	H410: Very toxic to aquatic life with long lasting effects.
	H411: Toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
	R7: May cause fire.
	R20: Harmful by inhalation.
	R21/22: Harmful in contact with skin and if swallowed.
	R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

LOCKFAST R20

		Page:	9
	R23: Toxic by inhalation.	J	÷
	R33: Danger of cumulative effects.		
	R34: Causes burns.		
	R36/37/38: Irritating to eyes, respiratory system and skin.		
	R43: May cause sensitisation by skin contact.		
	R48/20/22: Harmful: danger of serious damage to health by prolonged exposure		
	through inhalation and if swallowed.		
	R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the		
	aquatic environment.		
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquat	c	
	environment.		
	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the		
	aquatic environment.		
Legend to abbreviations:	PNEC = predicted no effect level		
	DNEL = derived no effect level		
	LD50 = median lethal dose		
	LC50 = median lethal concentration		
	EC50 = median effective concentration		
	IC50 = median inhibitory concentration		
	dw = dry weight		
	bw = body weight		
	cc = closed cup		
	oc = open cup		
	MUS = mouse		
	GPG = guinea pig		
	RBT = rabbit		
	HAM = hamster		
	HMN = human		
	MAM = mammal		
	PGN = pigeon		
	IVN = intravenous		
	SCU = subcutaneous		
	SKN = skin		
	DRM = dermal		
	OCC = ocular/corneal		
	PCP = phycico-chemical properties		
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive		
	and shall be used only as a guide. This company shall not be held liable for any		
	damage resulting from handling or from contact with the above product.		