

## Product

UV treated tape with very strong acrylic adhesive layer on one side.

## Application examples

- sealing of roofs (inside as well as outside)
- sealing of formworks
- airtight connections between vapour barriers
- taping cracks between insulation panels

## Colour

White  
Black

## Thickness

± 0,29 mm (without protective film)

## Width

60 mm

## Length

25 meter

## Packaging

On rolls  
In boxes, separated by a silicone paper

## Protection of adhesive layer

Yellow siliconized paper

## Properties

- ✓ good resistance to aging and to moisture
- ✓ very good resistance to plasticizers (test needed in advance)
- ✓ applicable from -10°C (dry surfaces)
- ✓ solvent-free adhesive layer

## Remark

All materials and substrates must be dry, free of grease, oil and dust.



## Technical properties

Property	Value + unit
Base	special UV treated tape
Adhesive	acrylic dispersion without solvents
Thickness (without protective film)	± 0,29 mm
Adhesion (DIN EN 1939)	± 35 N/25 mm
Aging resistance	very good
Moisture resistance	very good
Resistance to plasticizers	very good
UV stability	12 months (Central European sunlight)
Application temperature	> -10°C (dry, non-frozen surface)
Temperature resistance	-40°C to +100°C
Shelf life	24 months after production date
Storage	In original packaging at room temperature

## Note

The details and information given in this literature are based on best current knowledge. They are intended to serve as general information only and it is advised that the user conducts their own tests for their specific set of conditions to determine the suitability of the product for its proposed use. No warranty or liability is given or implied regarding any part of these instructions or details, or the completeness of the information.

We reserve the right to modify, or change, the specifications and information without advance notification.

All goods are supplied subject to our standard conditions of sales, copies of which are available upon request.

Technical data of supplier: 07-2013

The producer reserves the right to make changes. 2019 04 29