

Producten

Adhesive sealant NOVOPROOF® FA



A one component adhesive sealant made of synthetic rubber, which cures to a durable elastic rubber.

Especially developed for bonding and sealing NOVOPROOF® FA EPDM to most common building materials such as aluminium (untreated, anodised, powder coated), mineral substrates (concrete, stone, clinker, plaster), PVC windows, steel (galvanised, powder coated), wood (pre-testing), overlaps between EPDM films. Colour: black.
Packaging: 600 ml aluminium sausages
Consumption: 60 ml/running meter on 8 cm

NOVOPROOF® Cleaner



To clean the EPDM FA (if not clean enough) before bonding with the adhesive sealant FA or the contact adhesive Kleber TA.

NOVOPROOF® Primer



Adhesion promoter for using the Kleber TA contact adhesive or the Kleber FA adhesive sealant on a porous, damp substrate or when applied at temperatures between +3°C and -10°C.
Consumption: 10-15 gr/ meter on 5 cm

NOVOPROOF® Kleber TA



Contact adhesive based on synthetic rubber used for adhesion of the foil on all types of surfaces (wood, aluminium and stone).
Colour : black.

Consumption:

- 400 - 600 gr/m²
- 50 gr/rm on 8 cm

Certificate



Technical properties

Property Kleber TA	Value + unit
Colour	black
Density	0,85 kg/l
Dry solids	43,30 %
Flashpoint	-15°C
Viscosity	400 mPa.s +/- 100
Packaging	4,7 kg
Storage	12 months
Property Kit FA	Value + unit
Colour	black
Density	1,15 kg/l
Dry solids	79 %
Flashpoint	-8°C
Viscosity	4.500 mPa.s +/- 1.000
Packaging	600 ml – 12/doos
Storage	12 months
Property Primer	Value + unit
Colour	black
Density	0,835 kg/l
Dry solids	36,30 %
Flashpoint	-18°C
Viscosity	900 mPa.s +/- 100
Packaging	4,5 kg
Storage	12 months
Certificate	ATG 2891

Note

Always use a hard pressure roller for optimal adhesion. Two types are available: hard silicone rubber or steel.



Note

The information contained in this document is provided in good faith and is believed to be correct. However, we have no influence on the conditions in which these products are used or the methods by which they are used. Therefore, this information is not a substitute for tests which the customer must perform himself/herself in order to ensure that the products are safe, effective and achieve the intended purposes. Suggestions regarding the use of the product must not be used as grounds for infringement of any patent whatsoever. The only guarantee Castelein Sealants offers is that this product complies with the Castelein Sealants terms and conditions of sale in force at the time of shipment. Your only remedy in the event of a breach of this guarantee is the refund of the purchase price or the replacement of the product that does not comply with the guarantee.

Technical data of supplier: 2012

The producer reserves the right to make changes. 2020 04 01