

QTA-152 High Tack Fast Drying Contact Adhesive - 22kg Canister



Features

- Speed of application
- Self contained maintenance free
- Low odour
- Fast drying time
- Even coverage
- Moisture resistant
- Long lasting high tack adhesion

Technical Data

- Coverage approximately 500m² Higher coverage achieved on perfect or metal access floors
- Appearance clear liquid
- Very low VOC's Classified A+ Global compliant.
- Non flammable
- Solvent free
- Water based
- Shelf Life 6 months.
- Storage Temperature Above 5 deg C
- DO NOT ALLOW TO FREEZE

Surface Preparation

All surfaces must be clean, dry and free from oil, grease and paint. Any excessive dust must be removed as failure to do so will impair the performance of the adhesion. If applying the adhesive directly on to concrete, or sand and cement screeds, they must be fully cured and laitance free. If applying to earth subfloors an efficient damp proof membrane must be incorporated. Site conditions must comply with British Standards CP 102 (Code of practice for protection of building against water from underground), BS 5325 (Installation of textile floor coverings) and all supplementary publications must be followed throughout the installation.

If the system is to stand unused for a while then it is advisable to flush it out with GUNWASH so it is ready for instant use in the future.

It is the users responsibility to ensure that the adhesive is suitable for the substrates to be bonded, if you are unsure please contact our technical department for assistance.

