

Declaration of performance

Majvest 200 8910-150050/300050

Majvest 200 SOB 8915-150050 – Vers.1.0

Nr. DoP-21-891-00



1. Unique identification code of the product-type

8910-150050
8910-300050
8915-150050

2. Product labeling

Majvest 200
Majvest 200 SOB

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Flexible sheets for waterproofing - Underlays – Part 2: Underlays for walls; EN 13859-2

4. Name and contact address of the manufacturer:

SIGA Cover AG
Rütmattstrasse 7
6017 Ruswil
Switzerland

5. Name of the authorized representative whose mandate covers the tasks specified in Article 12, Paragraph 2:

Sylvia Flaig – Head of Quality Management

6. System of assessment and verification of constancy of performance of the construction product:

AVCP 3

7. Notified body:

TECHNICKY A SKUSOBNY USTAV STAVEBNY n.O.
NB 1301

has done the assessment and verification for system "3" and issued the following:

* test reports

8. Declared Performance:

Essential characteristics	Performance	Bottom tolerance	Top tolerance	Unit	Test Standard
Length	50	50	50.5	m	EN 1848-2
Width	1500	1497	1503	mm	EN 1848-2
	3000	2985	3045		
Mass per unit area (grammage)	146	141.9	160.5	g/m ²	EN 1849-2
Reaction to fire	E			Class	EN 13501-1
Watertightness	W1			Class	EN 1928
Water vapour transmission properties sd-value	0.05	0.02	0.09	m	EN ISO 12572
Tensile property max. force (MD)	315	250	400	N/50mm	EN 12311-1
Tensile property max. force (CD)	220	200	300	N/50mm	EN 12311-1
Tensile property elongation (MD)	60	40	110	%	EN 12311-1
Tensile property elongation (CD)	70	50	110	%	EN 12311-1
Resistance to tearing (nail tearing) (MD)	180	150	280	N	EN 12310-1

Resistance to tearing (nail tearing) (CD)	220	150	300	N	EN 12310-1
Cold bending behaviour	- 40			°C	EN 1109
Tensile property max. force (MD) (after artificial ageing)	295	204	345	N/50mm	EN 13859-1:2014 (C)** / EN 12311-1
Tensile property max. force (CD) (after artificial ageing)	225	143	275	N/50mm	EN 13859-1:2014 (C)** / EN 12311-1
Tensile property elongation (MD) (after artificial ageing)	45	25	95	%	EN 13859-1:2014 (C)** / EN 12311-1
Tensile property elongation (CD) (after artificial ageing)	47	30	97	%	EN 13859-1:2014 (C)** / EN 12311-1
Watertightness (after artificial aging)	W1			Class	EN 13859-1:2014 (C)** / EN 1928
watertightness against driving rain	passed				EN 13162
Hazardous substances	none				

** Increased requirement (according to ZVDH) at 80 °C

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance (DOP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by

Sylvia Flaig – Head of Quality Management



Sylvia Flaig (Jan 17, 2022 13:12 GMT+1)

Ruswil